



SAFETY DATA SHEET
Golden Film SAE 40 Classic Motor Oil

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME Golden Film SAE 40 Classic Motor Oil
 PRODUCT NO. 7454
 INTERNAL ID 10668
 APPLICATION Engine oil
 SUPPLIER Morris Lubricants
 Castle Foregate
 Shrewsbury
 SY1 2EL
 T: (+44)(0)1743 232200
 F: (+44)(0)1743 353584
 sds@morris-lubricants.co.uk

2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
zinc alkyl dithiophosphate	272-028-3		< 1%	Xi;R41. N;R51/53.

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

The Data Shown is in accordance with the latest EC Directives.

4 FIRST-AID MEASURES

GENERAL INFORMATION

Get medical attention if any discomfort continues.

INHALATION

In case of inhalation of spray mist: Move person into fresh air and keep at rest. Get medical attention if any discomfort continues.

INGESTION

Get medical attention if any discomfort continues. Do not induce vomiting.

SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water.

EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Get medical attention promptly if symptoms occur after washing.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Extinguish with foam, carbon dioxide, dry powder or water fog.

SPECIAL FIRE FIGHTING PROCEDURES

Keep run-off water out of sewers and water sources. Dike for water control.

UNUSUAL FIRE & EXPLOSION HAZARDS

Heat from fire could result in drums bursting

PROTECTIVE MEASURES IN FIRE

Self-contained breathing apparatus.

6 ACCIDENTAL RELEASE MEASURES

Golden Film SAE 40 Classic Motor Oil

PERSONAL PRECAUTIONS

For personal protection, see section 8. In case of spills, beware of slippery floors and surfaces.

ENVIRONMENTAL PRECAUTIONS

Contain spillage with sand or earth. Do not allow to enter drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.

SPILL CLEAN UP METHODS

Contain spillage with sand or earth. Use sealed containers for reclamation or disposal in licensed special waste. Avoid contact with water. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place.

STORAGE CLASS

Miscellaneous hazardous material storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs	STEL - 15 min	Notes
Mineral oil solvent dewaxed.	ACGIH	5 mg/m3	10 mg/m3	

ACGIH = American Conference of Governmental Industrial Hygienists.

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Use engineering controls to reduce air contamination to permissible exposure level.

ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

HAND PROTECTION

The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

OTHER PROTECTION

Use barrier creams to prevent skin contact.

HYGIENE MEASURES

Wash promptly with soap & water if skin becomes contaminated.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Amber to Brown		
ODOUR	Characteristic Oil smell		
SOLUBILITY	Insoluble in water Soluble in Organic solvents.		
BOILING POINT (°C)	>320	MELTING POINT (°C)	<-15
RELATIVE DENSITY	0.888 15	VAPOUR DENSITY (air=1)	>1
VAPOUR PRESSURE	<0.1 kPa 20	VISCOSITY	150 cSt 40
FLASH POINT (°C)	>200 PM Closed cup.		

Golden Film SAE 40 Classic Motor Oil

AUTO IGNITION

Not determined

TEMPERATURE (°C)

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

MATERIALS TO AVOID

Strong oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

11 TOXICOLOGICAL INFORMATION

GENERAL INFORMATION

This product has low toxicity. Only large volumes may have adverse impact on human health.

INHALATION

Unlikely to be hazardous by inhalation because of the low vapour pressure of the substance at ambient temperature.

INGESTION

No harmful effects expected in amounts likely to be ingested by accident.

SKIN CONTACT

Skin irritation is not anticipated when used normally. Repeated exposure may cause skin dryness or cracking.

EYE CONTACT

May cause temporary eye irritation.

SPECIFIC EFFECTS

Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis and skin cancer.

12 ECOLOGICAL INFORMATION

MOBILITY

The product is non-volatile. The product is insoluble in water and will spread on the water surface.

BIOACCUMULATION

Bioaccumulation is unlikely to be significant because of the low water solubility of this product.

DEGRADABILITY

The product is not readily biodegradable.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

GENERAL

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

15 REGULATORY INFORMATION

RISK PHRASES

NC Not classified.

SAFETY PHRASES

P13 Safety data sheet available for professional user on request.

UK REGULATORY REFERENCES

Health and Safety at Work Act 1974.

Golden Film SAE 40 Classic Motor Oil

EU DIRECTIVES

Dangerous Preparations Directive 1999/45/EC. Dangerous Substance Directive 67/548/EEC.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

REVISION COMMENTS

NOTE: Lines within the margin indicate significant changes from the previous revision.

REVISION DATE 01/02/2010

REV. NO./REPL. SDS GENERATED 1

RISK PHRASES IN FULL

R41 Risk of serious damage to eyes.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in a process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.